

STREET NAME SIGN
(CROSS STREET)

STREET NAME
BLADE POST
EXTENSION
24" LENGTH
1 1/2" SQUARE

SPACER .280" ID X .500" OD
LENGTH 1 3/4"
LONG BLACK PVC

CHERRYMATE RIVET
DIAMETER 1/4"
GRIP 1 5/8"
1 7/8" DOUBLE HEAD DESIGN
ALUMINUM



1" GAP

2 1/4" ZINC
CARRIAGE
BOLT FLUTED
TAMPER
RESISTANT
ALUMINUM,
5/16" NUT



BOTTOM OF SIGN

2 1/4" ZINC
CARRIAGE BOLT
FLUTED TAMPER
RESISTANT
ALUMINUM, 5/16" NUT

1 3/4" SQUARE 14
GAUGE/GALV.

7'-0" MIN

5/16" CORNER
BOLT & NUT

2' MIN.

5 HOLES OF
ANCHOR VISIBLE
ABOVE GROUND

FINISHED GRADE

9 HOLES
MINIMUM OF
POST WITHIN
ANCHOR

CURB AND GUTTER STREET

2'-7"

12" GAUGE ANCHOR SLEEVE
(8" X 2.25" X 2.25")

CLASS B CONCRETE

12" GAUGE ANCHOR SLEEVE
(36" X 2" X 2")

12" MIN. TYP.

DUCT TAPE BOTTOM & SIDES
OF SLEEVE & ANCHOR TO
PREVENT CONCRETE INFLOW

6"

NOTE:

1. ALL SIGNAGE SHALL BE INSTALLED IN ACCORDANCE WITH THE LATEST EDITION OF THE TEXAS MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (TMUTCD) AND THE STANDARD HIGHWAY SIGN DESIGN FOR TEXAS (SHSD).
2. LOCATIONS SHOWN FOR THE SIGNAGE ARE APPROXIMATE; FINAL LOCATIONS IN THE FIELD MAY CHANGE DUE TO POST CONSTRUCTION CONDITIONS AND PRESENCE OF OTHER PHYSICAL FEATURES. FINAL LOCATION OF ALL SIGNAGE SHALL BE FIELD VERIFIED WITH CITY PRIOR TO INSTALLATION.
3. ALL SIGNS SHALL HAVE 3M DG3 4000 SERIES REFLECTIVITY SHEETING AND THE SIZES SHALL BE STANDARD UNLESS OTHERWISE NOTED.
4. STOP SIGNS THAT WILL ACCEPT FUTURE STREET SIGNS SHALL HAVE A 24 INCH LONG STREET NAME BLADE POST EXTENSION OF 1 1/2 INCH BY 1 1/2 INCH O.D. SQUARE TUBING AS SHOWN ON THIS DETAIL. (THE STREET NAME BLADE POST EXTENSION SHALL BE 36 INCHES LONG IF SIGN TOPPERS ARE ALSO TO BE INSTALLED).



**PAVING CONSTRUCTION DETAILS
SIGN POST AND MOUNTING DETAILS**

REVISION DATE:
2/1/2024

SHEET: P-33